



KPS Accu-Cut 400 Step-Lap Core Cutting Line

Specifications:

Lamination Width : 40mm to 440mm

Decoiler : Single Head & Manual Expansion

Decoiler Options : Double Head, Hydraulic Expansion

Max Feed Rate : 240 Mtr/Min, upto 48 Sheets/Min.

Accuracy : ± 0.1 mm

Punch : Fixed Punch on Center Line, 8 to 35mm Hole Dia, Servo Tool Activation

V-Notch : In-out travel and tool activation with servo motors

Swing Shear : 45° / 90° / 135° Swing Position and Tool Activation with Servo Motors

Configurations : Vertical Step Lap / Horizontal Step Lap / Butt Lap
3,4,5 Legged Yoke / Leg / Center Leg



Features:

- ☒ Highest Through-Put
- ☒ Operator Friendly Software Interface
- ☒ Low Maintenance
- ☒ 3 Decades Expertise
- ☒ Life Cycle Service

Main Machine with Built-in Electrical Control System Offers Compact Foot print and **One Day Installation**



Stacker Type

High Speed In-Line
Magnetic Stacker

Stacking Positions

Under 40" 4 Positions,
Above 40" 2 Positions

Stacking

Without Pins on Pallets
(Accuracy $\pm 0.5\text{mm}$) or
Stacking on Pins

Stacking Cars

Automatic Car Positioning
Unloading Manually by
Operator

Contact KPS Sales team for any additional options

India Office:

Tel.: +91-99300-44314

Email: Automation@LIVE.com

KPS Machinery LLC

1733, Knight Bridge Dr, Newton, NC, USA 28658.

Phone: +1-828-461-5580 | Email: mike2000@charter.net

www.kpsmachinery.com

Serbia Office:

Tel.: +381-64-132 6070

Email: z.crncevic@mehatronik.com