



KPS Accu-Cut 600 Step-Lap Core Cutting Line

Specifications:

Lamination Width : 100mm to 640mm

Decoiler : Double Head or Hydraulic Expansion, Loop Pit Not Required

Decoiler Options : Four Head

Max Feed Rate : 240 Mtr/Min, upto 60 Sheets/Min.

Accuracy : ± 0.1 mm

Punch : Two Movable Punches Fixed on Center Line, 8 to 35mm Dia, Servo Tool Activation

V-Notch : In-out Travel and Tool Activation with Servo Motors

Swing Shear : 45° / 90° / 135° Swing Position and Tool Activation with Servo Motors

Configurations : Vertical Step Lap / Horizontal Step Lap / Butt Lap
3,4,5 Legged Yoke / Leg / Center Leg



Features:

- ☒ Highest Through-Put
- ☒ Operator Friendly Software Interface
- ☒ Low Maintenance
- ☒ 3 Decades Expertise
- ☒ Remote Diagnostics
- ☒ Life Cycle Service

Main Machine with Stand alone Electrical Control System, Double Head Decoiler, Two Punches, V- Notch, Helper Feeder & Swing Shear



Stacker Type

Two High Speed In-Line Magnetic Stackers with Divertor and By-pass

Stacking Positions

Under 60" 4 Positions, Above 60" 2 Positions

Stacking

Stacking on Pins

Two Stacking Cars

Automatic Car Positioning
Unloading Manually by Operator

Contact KPS Sales team for any additional options

India Office:

Tel.: +91-99300-44314
Email: Automation@LIVE.com

KPS Machinery LLC

1733, Knight Bridge Dr, Newton, NC, USA 28658.
Phone: +1-828-461-5580 | Email: mike2000@charter.net
www.kpsmachinery.com

Serbia Office:

Tel.: +381-64-132 6070
Email: z.crncevic@mehatronik.com